

## COMBO SELECTION GUIDE

Code	Description	Pipe Size Metric	Pipe Size Imperial	Roof Pitch	Base mm	Inches	Colours
DC100	Dektite Combo # mini	0-35mm	0-13/8"	0-45° or 12/12	99x99mm	39"	Black (EPDM)* Grey (EPDM)* Red Silicone*
DC101	Dektite Combo #1	5-65mm	¼ - 2½"	0-40° or 10/12	137x137mm	64"	
DC102	Dektite Combo #2	45-80mm	1¾ - 3¼"	0-40° or 10/12	177x177mm	69½"	
DC103	Dektite Combo #3	5-127mm	¼ - 5"	0-40° or 10/12	218x218mm	85¾"	
DC104	Dektite Combo #4	73-160mm	3-6¼"	0-40° or 10/12	284x284mm	111¾"	
DC105	Dektite Combo #5	108-190mm	4¼ - 7½"	0-40° or 10/12	365x365mm	143½"	
DC106	Dektite Combo #6	125-230mm	5-9"	0-40° or 10/12	365x365mm	143½"	
DC107	Dektite Combo #7	150-280mm	6-11"	0-40° or 10/12	453x453mm	178½"	
DC108	Dektite Combo #8	175-330mm	7-13"	0-40° or 10/12	453x453mm	178½"	
DC109	Dektite Combo #9	254-483mm	10-19"	0-40° or 10/12	685x685mm	269¾"	
DC Clip	Combo Clips Twin	25 Twins					

### Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roofline of -50°C (-122°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite® Silicone range go to [www.deks.com.au](http://www.deks.com.au) for more information on the full range.



**Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.**