

Installation Information



1

Trim the cone to suit pipe size using sharp tin snips.

"When piercing the tip of the cone of DFE 0-35, with a pen or pencil, a wire of up to 8 mm can be pushed through".



2

Slide down pipe using water as a lubricant.



3

Apply sealant by turning back flexible flange.



4

Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration.



5

Fasten using self-sealing fasteners or pop (sealed) rivets.



*

A Dektite® maybe fitted on the 'diamond' for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations.

EASY SELECTION GUIDE

Code No	Pipe mm	Pipe inch	Base mm	Inches	Pitch	Colours
DFE 0-35	0-35MM	0-1 ³ / ₈ "	99 X 99	39"	0-60° OR 1 ⁸ / ₁₂	Black (EPDM)* Grey (EPDM)* Red Silicone
DFE 5-55	5-55MM	1/4 - 2 ¹ / ₈ "	137 X 137	54"	0-45° OR 1 ² / ₁₂	
DFE 5-120	5-120MM	1/4 - 4 ³ / ₄ "	218 X 218	85 3/4"	0-45° OR 1 ² / ₁₂	
DFE 50-70	50-70MM	2 - 2 ³ / ₄ "	177 X 177	69 1/2"	0-45° OR 1 ² / ₁₂	
DFE 110-170	110-170MM	4 ¹ / ₂ - 6 ³ / ₄ "	284 X 284	111 3/4"	0-45° OR 1 ² / ₁₂	
DFE 160-220	160-220MM	6 ¹ / ₄ - 8 ³ / ₄ "	365 X 365	143 1/2"	0-45° OR 1 ² / ₁₂	
DFE 160-300	160-300MM	6 ¹ / ₄ - 11 ³ / ₄ "	453 X 453	178 1/2"	0-45° OR 1 ² / ₁₂	
DFE 290-440	290-440MM	11 ¹ / ₂ - 17 ³ / ₈ "	581 X 581	228 1/2"	0-45° OR 1 ² / ₁₂	

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roofline of -50°C (-112°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite® Silicone range. Go to www.deks.com.au for more information on the full range.

Features



Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.