

## Installation Information



1

Trim the cone to suit pipe size using sharp tin snips.



2

Slide down pipe using water as a lubricant.



3

Apply sealant by turning back flexible flange.



4

Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration.



5

Fasten using self-sealing fasteners or pop (sealed) rivets.



\*

A Dektite® may be fitted on the 'diamond' for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations.

## EASY SELECTION GUIDE

### Premium Square Base

Code No	Pipe External	Pitch	
DFE 0-35RE	0-35mm	0-1 $\frac{3}{8}$ "	Red Silicone
DFE 5-55RE	5-55mm	$\frac{1}{4}$ - 2 $\frac{1}{8}$ "	
DFE 5-120RE	5-120mm	$\frac{1}{4}$ - 4 $\frac{3}{4}$ "	
DFE 50-70RE	50-70mm	2 - 2 $\frac{3}{4}$ "	
DFE 110-170RE	110-170mm	4 $\frac{1}{2}$ - 6 $\frac{3}{4}$ "	
DFE 160-220RE	160-220mm	6 $\frac{1}{4}$ - 8 $\frac{3}{4}$ "	
DFE 160-300RE	160-300mm	6 $\frac{1}{4}$ - 11 $\frac{3}{4}$ "	
DFE 290-440RE	290-440mm	22-22"	

Silicone withstands temperatures from -50°C (-122°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

### Original Round Base

Code No	Pipe External	Pitch	
DF201RE	5-65mm	$\frac{1}{4}$ - 2 $\frac{1}{2}$ "	Red Silicone
DF202RE	45-80mm	1 $\frac{3}{4}$ - 3 $\frac{1}{4}$ "	
DF203RE	5-127mm	$\frac{1}{4}$ -5"	
DF204RE	73-160mm	3-6 $\frac{1}{4}$ "	
DF205RE	108-190mm	4 $\frac{1}{4}$ - 7 $\frac{1}{2}$ "	
DF206RE	125-230mm	5-9"	
DF207RE	150-280mm	6-11"	
DF208RE	175-330mm	7-13"	
DF209RE	254-483mm	10-19"	

Silicone withstands temperatures from -50° C (-122°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

When there is a concern for heat, silicone dektites can be used for single skin flues and stoves to temperatures specified.