



Installation Information

1. Easy to shape and mount

PERFORM flexible flashing is fixed easily and fast. The light weight and the excellent stretching properties ensure simple handling and shaping of the flashing. To obtain, a perfect fit use a Perform hammer.

2. Placing the flashing material

The side with the protection film is the visible or upper side of the material. This is to prevent the flashing material from getting dirty.

3. Fold on edge

By folding the bottom edge it becomes significantly stronger and the roof covering then becomes even more stable in shape.

4. Fixing without adhesives

PERFORM flexible flashing is fitted without use of adhesive since the material is self-contained like lead. A self-contained flashing is porous/breathable and prevents formation of humidity and condensation under the area covered.

5. Fixing using adhesion

When ever deemed necessary you can make terminations against walls, roofs, valley gutters etc. For adhesive process use Z BOND Metal & Masonry Silicone V4. Spot adhesion technique is recommended.

EASY SELECTION GUIDE

Accessories

Perform Hammer **CODE: Hammer**

Rolls

| Product Code | Length | Width | Weight |
|--------------|-----------|--------------|--------------------|
| PFR4-300G | 4m or 13' | 300mm or 12' | 4.32kg or 9.5lbs |
| PFR4-300RE | 4m or 13' | 300mm or 12' | 4.32kg or 9.5lbs |
| PFR4-300B | 4m or 13' | 300mm or 12' | 4.32kg or 9.5lbs |
| PFR4-400G | 4m or 13' | 400mm or 15' | 5.76kg or 12.67lbs |
| PFR4-400RE | 4m or 13' | 400mm or 15' | 5.76kg or 12.67lbs |
| PFR4-400B | 4m or 13' | 400mm or 15' | 5.76kg or 12.67lbs |
| PFR4-450G | 4m or 13' | 450mm or 18' | 6.48kg or 14.26lbs |
| PFR4-450RE | 4m or 13' | 450mm or 18' | 6.48kg or 14.26lbs |
| PFR4-450B | 4m or 13' | 450mm or 18' | 6.48kg or 14.26lbs |
| PFR4-600G | 4m or 13' | 600mm or 24' | 8.64kg or 19.16lbs |
| PFR4-600RE | 4m or 13' | 600mm or 24' | 8.64kg or 19.16lbs |
| PFR4-600B | 4m or 13' | 600mm or 24' | 8.64kg or 19.16lbs |

Available in G-Grey RE-Red B-Black

Sheets

| Product Code | Length | Width | Weight |
|--------------|--------------|--------------|---------------------|
| PFS410-490 | 410mm or 16' | 490mm or 19' | 700grams or 1.5lbs |
| PFS450-600 | 450mm or 18' | 600mm or 24' | 920grams or 2.03lbs |
| PFS600-600 | 600mm or 24' | 600mm or 24' | 1.24kgs or 2.72lbs |

Available in G-Grey RE-Red B-Black

The future is lead free...

IMPORTANT:

- Remember to place the flashing material correctly according to the actual need for stretching ability.
- Cut the flashing by means of trade knife or sheet metal shears.
- When pre-fixing and shaping joints are required, use adhesive, if deemed necessary.
- Use the PERFORM hammer to dress down leading edges.
- If painting is required, we recommend 100% Acrylic Low Sheen exterior paint.
- When lapping joints, 150mm (6") overlap is recommended.
- Perform has the ability to expand and contract, thus allowing minimal joints.