

Nu Lead - For Tiled Roofs



No more worries about unprotected lead

Combines a long-life weather resistant EPDM cone with grey primed Thermo-Baked Acrylic Primer coating. The unique thermo baked coating does not affect the lead's malleability, and prevents leaching onto the roof and into the gutter, down pipes and the water table.

Pipe External mm	Lead Sheet Size mm	Product Code	Carton Qty
0-8	410 x 490	DNLS10MB	4
0-30	410 x 490	DNLS100B	4
12-70	410 x 490	DNLS101B	4
50-70	450 x 600	DNLS102B	4
50-70	410 x 490	DNLS102B	4
5-127	410 x 490	DNLS113B	1
50-170	450 x 600	DNLS103B	4
50-170	410 x 490	DNLS103B	4
175-330	550 x 850	DNLS108B	1

Available in Black EPDM and Red Silicone with grey lead base.

Fast Flash



Self Adhesive lead replacement

Fast Flash is ideal for anywhere requiring a quick and secure flashing solution. Fast Flash can be installed on roofs with a slope of min. 5° and on almost all roof materials. Fast Flash has the added benefit of being environmentally friendly and comes in various sizes.

Width	Length	Weight	Colour	Product Code
260mm or 11"	5m or 16'	4.7kg or 10lb	Grey/Black and Red Brick	FFR5-280
370mm or 12.5"	5m or 16'	4.7kg or 10lb	Grey/Black and Red Brick	FFR5-370
560mm or 20"	5m or 16'	9.2kg or 20lb	Grey/Black and Red Brick	FFR5-560

For detailed installation information go to: www.deks.com.au/products/main-products/non-lead-flashings

Dekstrip



Stretches to any Shape, Seals and Stays

Forms and stretches to solve all your flashing problems. Dekstrip expandable edge flashing is the answer to flashing large, curved, curved, curved and penetrations. It's ideal for box gutter expansion joints and is the fast, easy & most effective way to flash a bullnose.

Width	Length	Product Code	Carton QTY
180mm or 7"	23m or 75'	DS23-180	1
235mm or 9"	23m or 75'	DS23-235	1
305mm or 12"	23m or 75'	DS23-305	1
180mm or 7"	10m or 33'	DS10-180	1
235mm or 9"	10m or 33'	DS10-235	1
305mm or 12"	10m or 33'	DS10-305	1
235mm or 9"	3m or 10'	DS3-235	1
450mm or 18"	15m or 50'	DS15-450	1

Available in Grey EPDM.

For detailed installation information go to: www.deks.com.au/products/main-products/dekstrip-flashings

PERFORM



Lead Free Flashing

The future is lead free. Perform is environmentally friendly as it is made of aluminium sheeting coated with polymer rubber. It is 1/3 the weight of lead which allows for fast and easy mounting.

Width	Length	Weight	Product Code
300mm or 12"	4m or 13'	4.32kg or 9.5lbs	PFR 4-300
400mm or 15"	4m or 13'	5.76kg or 12.67lbs	PFR 4-400
450mm or 18"	4m or 13'	6.48kg or 14.28lbs	PFR 4-450
600mm or 24"	4m or 13'	8.64kg or 19.16lbs	PFR 4-600
490mm or 19"	410mm or 16"	700g or 1.5lbs	PFS410-490
600mm or 24"	450mm or 13"	920g or 2.03lbs	PFS450-600
900mm or 24"	600mm or 24"	1.24kg or 2.72 lbs	PFS600-600

Available in Black, Grey and Red. Also Available in a range of sheets.

Solar Solutions



Specialty flashing for solar panels

Designed specifically for solar panel installation on both metal and tile roofs. Fast. Efficient. Safe.

PV Installations

Roof Type	Pipe OD (mm)	Pipe OD (inch)	Base (mm)	Base (inch)	Product Code	Carton Qty
Metal	0-8 x 12	0 - 1/2" x 12	139 x 139	5 1/2" x 5 1/2"	DFE101BM	15
Tile	0-8 x 10	0 - 1/2" x 10	410 x 410	16 x 16	DNLS10MB	1
Tile	0-8 x 10	0 - 1/2" x 10	500 x 600	19 1/2" x 23 1/2"	SDA10MB	1

Hot Water Installations (Solar Thermal)

Roof Type	Pipe OD (mm)	Pipe OD (inch)	Base (mm)	Base (inch)	Product Code	Carton Qty
Metal	0-35	0 - 1 1/2"	100 x 100	4" x 4"	DFE100BS	20
Metal	5-55	1/2" - 2 1/4"	139 x 139	5 1/2" x 5 1/2"	DFE101BS	15
Tile	0-30	0 - 1 1/2"	410 x 490	16 x 19"	DNL100B	4

Specialty Products



Evaporative Cooler Flashing


Purpose designed polymer skirt for flashing the ductwork supporting evaporative cooler units. Long life polymer and durable 99.9% pure aluminium are used to manufacture flashings suitable for both tile and metal roof installations.

Tiled Roof

Product Code	Duct External	Base Sizes	Aluminium Colour
SDA550B	550 x 550mm	1040 x 1290	Plain
SDA550GB	550 x 550mm	1040 x 1290	Grey
SDA550REB	550 x 550mm	1040 x 1290	Red
SDA550GRB	550 x 550mm	1040 x 1290	Green

Metal Roof

Product Code	Duct External	Base Sizes	Carton Qty
DFE550B	550 x 550mm	854 x 723	1



Antenna Flashing

Self Adhesive lead replacement multicable Flashing. Easy to install and environmentally friendly!

Tiled Roof

Product Code	Pole Diameter	Base Sizes	Carton Qty
DFE10ABB	6mm - 50mm	280mm x 450mm	1



Deks Top Hat Roof Kit

The Top Hat Roof Kit consists of 6 components that create a roof penetration system which is quick and easy to install, saving you time and money. Our unique roof penetration kit ensures that all pipework goes through one penetration to meet regulatory requirements and to reduce the risk of roof leaks. It is the only product that directly caters for the penetration of HVAC, solar pipework, plumbing pipework, electrical conduits and cables.


Deks Code	Tube Diameter	Suits copper sizes					
		1/4" - 3/8" or 6.4-9.5mm	1/4" - 1/2" or 6.4-12.7mm	1/4" - 5/8" or 6.4-15.9mm	3/8" - 5/8" or 9.5-15.9mm	3/8" - 3/4" or 9.5-19mm	1/2" - 3/4" or 12.7-19mm
DTHRKIT65	65mm	✓	✓				
DTHRKIT80	80mm	✓	✓	✓	✓		
DTHRKIT110	110mm	✓	✓	✓	✓	✓	✓
DTHRKIT85TWIN	85mm	✓	✓				

DEKS
Easy to Work With

5/841 Mountain Hwy, Bayswater, Victoria, 3153. P.O. Box 569, Bayswater, Victoria, 3153
Phone: +61 (0)3 8727 8800 or 1800 882 098. Fax: +61 (0)3 9720 1000
Email: info@deks.com.au Web: www.deks.com.au
© Copyright, Published 2012

Need to flash it?

DEKS brings you the world's best flashing range



20 YEAR WARRANTY

DEKS
Easy to Work With

- Metal Chimneys • Hot & Cold Flues • Vents
- Refrigeration/air con connections • Antennas
- Conduits • Ducts • Wiring/cables

www.deks.com.au

Dektite® Premium™



Perfect for flashing pipes on metal roofs

A multi-application flashing with a highly durable EPDM cone and base, edged with a flexible aluminium strip, flashes hot or cold flues and pipes on metal roofs. The square base fits any prepared hole on most roofs profiles.

Pipe External	Base Sizes	Product Code	Carton Qty
0-20mm	0-1 1/2"	DFE10M*	20
0-35mm	0-1 1/2"	DFE100*	20
0-35mm	0-1 1/2"	DFE100*S	20
0-55mm	0-2 1/4"	DFE101*	15
0-55mm	0-2 1/4"	DFE101*S	15
0-8 mmx 12	0-3/4" x 12	DFE101*M	15
5-76mm	3/4 - 3"	DFE102*	15
50-70mm	2-2 3/4"	DFE102*A	15
5-127mm	3/4 - 5"	DFE103*	15
75-175mm	3 - 7"	DFE104*	10
100-200mm	4 - 8"	DFE105*	10
125-230mm	5 - 9"	DFE106*	10
150-300mm	6 - 12"	DFE107*	10
170-355mm	6 3/4 - 14"	DFE108*	5
230-508mm	9 - 20"	DFE109*	5

Available in Grey, Black EPDM and Red Silicone. * should be replaced with either 'B' for Black, 'G' for Grey or 'RE' for Red Silicone, 'S' = Solar (extra outlets)

Dektite® Original



The original watertight flashing for metal roofs

The original watertight flashing designed to seal both hot and cold flues and pipes on metal roofs. A strong water tight seal and a strong flexible base with the aluminium band.

Pipe external	Product Code	Roof pitch	Pipe external	Product Code	Roof pitch
0-35mm	DF100	0-45° or 1/2"	5-65mm	DF201RE	0-40° or 1/2"
5-65mm	DF101	0-40° or 1/2"	45-80mm	DF202RE	0-40° or 1/2"
45-80mm	DF102	0-40° or 1/2"	5-127mm	DF203RE	0-40° or 1/2"
5-127mm	DF103	0-40° or 1/2"	73-160mm	DF204RE	0-40° or 1/2"
73-160mm	DF104	0-40° or 1/2"	108-190mm	DF205RE	0-40° or 1/2"
108-190mm	DF105	0-40° or 1/2"	125-230mm	DF206RE	0-40° or 1/2"
125-230mm	DF106	0-40° or 1/2"	150-280mm	DF207RE	0-40° or 1/2"
150-280mm	DF107	0-40° or 1/2"	175-330mm	DF208RE	0-40° or 1/2"
175-325mm	DF108	0-40° or 1/2"	254-483mm	DF209RE	0-40° or 1/2"
254-483mm	DF109	0-40° or 1/2"			

EPDM will withstand constant temperature at the roofline of -50°C to 115°C (-122°F to 239°F) & up to 150°C (302°F) intermittently.

Silicone will withstand constant temperature at the roofline of -50°C to 200°C (-112°F to 392°F) & up to 250°C (482°F) intermittently.

For detailed installation information go to: www.deks.com.au/products/main-products/dek-lite-metal-roofs

Dektite® Combo™



Flash over or around

A standard Dektite and Retrofit all in one. Clips included.

Pipe External	Base Sizes	Product Code	Carton Qty
5-60mm	1/2 - 2 1/2"	DC101*C	20
45-80mm	1 1/4 - 3 1/4"	DC102*C	20
5-125mm	3/4 - 5"	DC103*C	10
73-160mm	3-7"	DC104*C	5
108-190mm	4 1/4 - 7 1/2"	DC105*C	5
125-230mm	5-9"	DC106*C	5
150-280mm	6-11"	DC107*C	5
175-330mm	7-13"	DC108*C	5
240-508mm	9 1/2 - 20"	DC109*C	2
400-750mm	15 3/4 - 29 1/2"	DC110*C	1
25 Twins		DC Clip	

Available in Grey, Black EPDM and Red Silicone. * should be replaced with either 'B' for Black, 'G' for Grey or 'RE' for Red Silicone

Combo Square Selection Guide

Pipe External	Base Sizes	Product Code	Carton Qty
20-125mm	3/4-5"	DCS103BC	5

Available in Black EPDM.

Lead Collar



For Flashings on tile and slate roofs

A pre fabricated acrylic lead flashing designed to save you time and money. The 425 x 425mm acrylic lead sheet has a pre fabricated 58mm opening designed for 50mm pvc. Suitable for all tiled and slate roofs.

Pipe External	Base Sizes	Product Code	Carton QTY
50mm or 2"	425 x 425mm or 16 1/2" x 16 1/2"	DLC425x425-50	5

Dektite® Ezi-Seal™



Forget Silicone just screw it down

Features a revolutionary non-absorbent and non porous sponge gasket that seals by compression, even in wet conditions, it hugs the roof line to provide a watertight seal without the need for silicone sealant.

Pipe External	Base Sizes	Pitch	Product Code	Carton Qty
0-35mm	0 - 1 1/2"	100 x 100mm 4 x 4"	DFE100BEZ	20
0-55mm	0 - 2 1/4"	139 x 139mm 5 1/2 x 5 1/2"	DFE101BEZ	15
5-76mm	3/4 - 3"	178 x 178mm 7 x 7"	DFE102BEZ	15
50-70mm	2 - 2 3/4"	178 x 178mm 7 x 7"	DFE102BAEZ	15
5-127mm	3/4 - 5"	221 x 221mm 8 3/4 x 8 3/4"	DFE103BEZ	15
75-175mm	3 - 7"	280 x 280mm 11 x 11"	DFE104BEZ	10
100-200mm	4 - 8"	310 x 310mm 12 1/4 x 12 1/4"	DFE105BEZ	10
125-230mm	5 - 9"	363 x 363mm 14 1/4 x 14 1/4"	DFE106BEZ	10
150-300mm	6 - 12"	456 x 456mm 18 x 18"	DFE107BEZ	10
170-355mm	6 3/4 - 14"	496 x 496mm 19 1/2 x 19"	DFE108BEZ	5
230-508mm	9 - 20"	681 x 681mm 23 x 23"	DFE109BEZ	5

Available in Black EPDM.

Dektite® Soaker-Diverter



For Hi/Low Roof Pitches

The large base of a Dektite Soaker dramatically reduces rainwater back up on very low or very high roof pitches and deep ribbed roofing profiles.

Pipe External	Base Sizes	Pitch	Product Code	Carton QTY
75-155mm	3 - 6"	410 x 350mm 16 x 14"	DF602	2
114-254mm	4 1/2 - 10"	485 x 460mm 19 x 18"	DF603	2
254-406mm	10 - 16"	708 x 640mm 27 3/4 x 25"	DF605	2
380-610mm	15 - 24"	1415 x 905mm 39 3/4 x 35 1/2"	DF606	1
235-425mm	9 - 16"	762 x 680mm 30 x 26 1/4"	RFS4	2

Available in Grey EPDM and Red Silicone.

For detailed installation information go to: www.deks.com.au/products/main-products/dek-lite-metal-roofs

Retrofit Original



For repairs & difficult to access pipes

Most commonly used when flashing around an existing penetration when going over the top of the pipe material is not an option. The unique patented zip lock does not require separate clips - just clamp it together.

Pipe External	Base Sizes	Pitch	Product Code	Carton QTY
20-70mm	1/2 - 2 1/4"	160mm 6 3/8"	RF801	10
50-190mm	2 - 7 1/2"	273mm 10 3/4"	RF802	5
85-255mm	3 1/4 - 10"	369mm 14 1/2"	RF803	5
235-425mm	9 1/4 - 16 1/4"	762 x 680mm 30 x 26 1/4"	RFS4	2
20-70mm	1/2 - 2 1/4"	160mm 6 3/8"	RF901	10
50-190mm	2 - 7 1/2"	273mm 10 3/4"	RF902	5
85-255mm	3 1/4 - 10"	369mm 14 1/2"	RF903	5
235-425mm	9 1/4 - 16 1/4"	762 x 680mm 30 x 26 1/4"	RFS24	2

Available in Grey and Black EPDM and Red Silicone.

For detailed installation information go to: www.deks.com.au/products/main-products/dek-lite-metal-roofs

Aluminium



For Flashings on tile and slate roofs

The SELDEK™ Aluminium™ won't stain or corrode spouting and gutters. The EPDM cone, which is trimmed on site to fit, is ingeniously locked to a high grade and malleable 99.9% pure aluminium base.

Pipe External	Base Sizes	Pitch	Product Code	Carton QTY
0-30mm	0 - 1 1/2"	500x600mm 19 1/4 x 23 3/4"	SDAMiniB	3
12-70mm	1/2 - 2 1/4"	500x600mm 19 1/4 x 23 3/4"	SDA100B	3
50-170mm	2 - 6 1/4"	500x600mm 19 1/4 x 23 3/4"	SDA101B	3
110-200mm	4 1/2 - 8"	500x600mm 19 1/4 x 23 3/4"	SDA102B	3
160-300mm	6 1/4 - 11 1/4"	764x764mm 30 x 30"	SDA103B	5
300-450mm	12 - 17 1/4"	956x956mm 37 x 37"	SDA104B	5

Available in Black EPDM.

Dekform



Lead Flashings No Longer Required

Designed as an environmentally friendly product eliminating concerns caused by using lead. Designed to suit all tiled roof flashing applications. A great product choice when Rain Water Harvesting is in use. Keep your water clean from contamination.

Pipe External	Sheet Size	Product Code	Pipe External	Sheet Size	Product Code		
0-30mm	0 - 1 1/2"	410 X 490mm 16 x 19"	DFM100GB	0-30mm	0 - 1 1/2"	410 X 490mm 16 x 19"	DFM200GR
12-70mm	1/2 - 2 1/4"	410 x 490mm 16 x 19"	DFM101GB	12-70mm	1/2 - 2 1/4"	410 x 490mm 16 x 19"	DFM201GR
50-70mm	2 - 2 1/4"	600 x 450mm 24 x 18"	DFM102GB	50-170mm	2 - 6 1/4"	600 x 450mm 24 x 18"	DFM203GR
50-170mm	2 - 6 1/4"	600 x 450mm 24 x 18"	DFM103GB				
175-330mm	7 - 13"	850 x 550mm 34 X 22"	DFM108GB				

